

セキサク標準ウイングスタビライザー寸法表

サイズ [inch]	坑井径 [mm]	ボデー外径 [mm] / (inch)	内径 [mm] / (inch)	接続ネジ	有効長 [mm]	重量 [Kg]
5-5/8	142.9	120.65 (4-3/4)	50.8 (2)	NC38 (3-1/2 IF)	1000	95
5-7/8	149.2	120.65 (4-3/4)	50.8 (2)	NC38 (3-1/2 IF)	1000	95
7-5/8	193.7	158.75 (6-1/4)	57.15 (2-1/4)	NC46 (4 IF)	1400	185
7-7/8	200.0	165.1 (6-1/2)	57.15 (2-1/4)	NC46 (4 IF)	1400	190
8-1/2	215.9	165.1 (6-1/2)	63.5 (2-1/2)	NC46 (4 IF)	1400	210
9-5/8	244.5	203.2 (8)	71.44 (2-13/16)	6-5/8 REG	1400	320
9-7/8	250.8	203.2 (8)	71.44 (2-13/16)	6-5/8 REG	1400	320
10-5/8	269.9	203.2 (8)	69.85 (2-3/4)	6-5/8 REG	1400	325
12-1/4	311.2	203.2 (8)	71.44 (2-13/16)	6-5/8 REG	1400	330
16	406.4	254 (10)	69.85 (2-3/4)	6-5/8 REG	1600	565
17-1/2	444.5	254 (10)	69.85 (2-3/4)	6-5/8 REG	1600	570
20	508.0	300	76.2 (3)	7-5/8 REG	1500	585
22	558.8	300	76.2 (3)	7-5/8 REG	1500	595
24	609.6	300	76.2 (3)	7-5/8 REG	1500	610
26	660.4	300	76.2 (3)	7-5/8 REG	1500	620